



9K BISDON ANKLE – (PU/PU)

Detail

The differences between Rubber and Polyurethane are heat and chemical resistance properties. Rubber soles give greater resistance. Shoes with rubber soles are therefore the correct choice for areas of application in which these kinds of hazards may arise. Vulcanized Nitrile Rubber can withstand temperature of 300° C. PU+Nitrile Rubber shoes provide comfort to the wearer. Polyurethane midsole gives cushioning effect and helps in energy absorption thereby increasing the work efficiency of the wearer.

Description

NAME: 9K BISDON ANKLE

UPPER MATERIAL: GENUINE LEATHER 1.8-2.0 MM THICKNESS

QUARTER LINING: Sweat absorbent grey/orange mesh having excellent abrasion resistance.

TOE CAP: Steel Toe Cap EN 12568 200J with Comfort Strip. Protect against compression injury up to 15 KN.

INSOLE: Anti-Static Insole.

MIDSOLE: Polyurethane (PU) Black colour serving as a Cushion for comfort.

OUTSOLE: Nitrile Rubber having excellent abrasion resistance and heat resistant up to 300° C.

INSOCKS: 4 mm soft EVA Insocks.

SIZE: UK 04 - UK 14

PROPERTIES: Anti-static, ANTI SKID, OIL & ACID RESISTANT, SHOCK ABSORBER AND HEAT RESISTANT UP TO 300° C

OPTIONAL: Polycarbonate Toe cap, Anti-penetration Kevlar/Steel mid plate.